

Ultrasonic Cleaning Systems for Medical and Industry

Product name	Code
SONICA 60L EP S3 *	090.003.0039
Ultrasonic Cleaner	
Accessories	
Stainless steel wire basket Internal dim. 1.070x290x150mm	090.004.0012
Stainless steel lid	090.004.0028
Stainless steel auxiliary tank SONICA 3300 Indicative dim. 300x240x150mm	090.004.0044

SONICA[®] 60 Litres



Further accessories on request

* Special stainless steel tank made in AISI 316Ti thickness 20/10 with round tank corners for a better removing of dirt residuals after cleaning process. The tank is welded with TIG process

General Characteristics

Ultrasonic Cleaning is a safe and efficient modern procedure, which ensures perfect cleaning within the shortest time possible. It has many advantages over ordinary cleaning methods. Ultrasonics can remove even the most tenacious deposits from parts which would be difficult to reach by hand, it also reduces the risk of injury or infection which may occur during manual cleaning.

Notes for use as "Medical Devices"

Denomination: Ultrasonic Cleaning Equipment EMDN: Z12011302 **Field of application**: Ultrasonic Cleaning Equipment for surgical and dental instruments **Classification**: Medical Devices Regulation Class I rule 13, Active MD, Non Invasive MD, Non Implantable MD

Product MDR compliant Regulation (EU) 2017/745

SOLTEC S.r.l.

Uffici Commerciali e Sede Legale: Via G. Röntgen 16 - 20136 Milano Tel. +39 02 58 308 378 - Fax +39 02 58 308 595 - www.soltec.it - info@soltec.it Produzione e Magazzino: Via G. Castelbarco, 17 - 20136 Milano - Tel. +39 02 58 324 131

Cod. fisc. e P.IVA: IT11127210158 N. Mecc.: MI 221750 - C.C.I.A.A. Milano N. 1441548 Iscr. Trib. Mi Reg. Soc. N. 343391/8444/41 Cap. Soc. Euro 110.500 i.v. - Iscr. Registro AEE Nr. IT0802000000435



SONICA® Lavatrici ad Ultrasuoni - SONICA® Ultrasonic Cleaners - SONICA® Ultraschall - Reinigungsgeräte



Technical Data

SONICA[®] 60 Litres

Technical specification subject to change

Main line voltage	230/240V~50/60Hz		
Main input power/consumption	700 W		
Main input power with heating	2200 W		
Peak HF Ultrasound Power	1400 W		
US frequency	39 kHz ± 1 kHz with SWEEP SYSTEM Technology		
Liquid drain	1/2"		
Transducers	16 (2 Piezoelectric ceramics each)		
Tank capacity [L]	60		
Weight [KG]	30		
Installation category	Class II according to EN 61010-1		
Environmental conditions	Temperature Rel. Hum. 80% up to 31°C with linear		
	decrease up to 50% at 40°C		
IP grade	IP 22		
CE-compliant	EMC (EN 61326-1)		
	LV (EN 61010-1 EN 61010-2-040)		
	2017/745/UE Medical Device Regulation		
	Risk Class I according to the rule 13 to the MDR		


Effective Tank Internal Dimensions

External Appliance Dimensions

W/D/H (mm)	1.100 / 300 / 200	W/D/H (mm)	1.160 / 360 / 425
Max filling volume tank	60 L	Max operating tank volume	56 L

Constructive Materials

Housing	Stainless steel AISI 304
Tank	Stainless steel AISI 316Ti 20/10



Control panel available series

Μ	MH	ETH	EP
	NOT AVAILABLE	NOT AVAILABLE	SONICA URACINC CLANCE
			EP serie : The most technologically advanced of the SONICA range: Sweep System generator; modern digital display control panel window; degas time setting; cleaning times from 0 to 99 minutes; tank liquid temperature setting up to 70°C; memory for 9 cleaning programmes; jet program function to start quickly and easily cleaning cycle.

SOLTEC Srl – Via G.Rontgen 16 – 20136 Milano – Italy- Tel +39 0258308378 - Fax +39 0258308595 info@soltec.it https://www.soltec.it Facebook https://www.facebook.com/soltec.ultrasonics LinkedIn https://www.linkedin.com/company/soltec-srl