

Ultrasonic Cleaning Systems for Medical and Industry

| Product name | Code |
|--|--------------|
| | |
| SONICA 2200 M S3 * | 090.003.0002 |
| SONICA 2200 MH S3 * | 090.003.0003 |
| SONICA 2200 ETH S3 * | 090.003.0004 |
| SONICA 2200 EP S3 * | 090.003.0005 |
| Ultrasonic Cleaner 3 Litres | |
| Accessories | |
| Stainless steel wire basket Internal dim. 205x110x45mm | 090.004.0002 |
| Stainless steel lid 2200 | 090.004.0018 |
| Stainless steel auxiliary tank SONICA 2200 Indicative dim. 240x140x100mm | 090.004.0040 |
| Stainless steel beaker holder for two glass or plastic beaker | 090.004.0035 |
| Plastic beaker 250 ml | 090.004.0032 |
| Glass beaker 400 ml | 090.004.0033 |
| Further accessories on reques | t |

SONICA[®] 2200 S3



Stainless steel tank made in AISI 304 thickness 08/10 with round tank corners for a better removing of dirt residuals after cleaning process. The tank is conical and realized with a press machine

General Characteristics

Ultrasonic Cleaning is a safe and efficient modern procedure, which ensures perfect cleaning within the shortest time possible. It has many advantages over ordinary cleaning methods. Ultrasonics can remove even the most tenacious deposits from parts which would be difficult to reach by hand, it also reduces the risk of injury or infection which may occur during manual cleaning.

Notes for use as "Medical Devices"

Denomination: Ultrasonic Cleaning Equipment EMDN: Z12011302 **Field of application**: Ultrasonic Cleaning Equipment for surgical and dental instruments **Classification:** Medical Devices Regulation Class I rule 13, Active MD, Non Invasive MD, Non Implantable MD

Product MDR compliant Regulation (EU) 2017/745

SOLTEC S.r.l.

Uffici Commerciali e Sede Legale: Via G. Röntgen 16 - 20136 Milano Tel. +39 02 58 308 378 - Fax +39 02 58 308 595 - www.soltec.it - info@soltec.it Produzione e Magazzino: Via G. Castelbarco, 17 - 20136 Milano - Tel. +39 02 58 324 131

Cod. fisc. e P.IVA: IT11127210158 N. Mecc.: MI 221750 - C.C.I.A.A. Milano N. 1441548 Iscr. Trib. Mi Reg. Soc. N. 343391/8444/41 Cap. Soc. Euro 110.500 i.v. - Iscr. Registro AEE Nr. IT0802000000435



SONICA® Lavatrici ad Ultrasuoni - SONICA® Ultrasonic Cleaners - SONICA® Ultraschall - Reinigungsgeräte



Rev.4-04-2024

SONICA[®] 2

Technical specification subject to change

| Incl | hnical | l llata |
|------|--------|---------|
| IELI | IIIICa | l Data |
| | | |

| Main line voltage | 230/240V~50/60Hz | |
|--|--|--|
| Main input power/consumption | 130 W | |
| Main input power with heating | 305 W | |
| Peak HF Ultrasound Power | 260 W | |
| US frequency | 39 kHz ± 1 kHz with SWEEP SYSTEM Technology | |
| Liquid drain | Mod. ETH-EP (tube 10x8mm) | |
| Transducers | 2 (2 Piezoelectric ceramics each) | |
| Tank capacity [L] | 3 | |
| Weight [KG] | 3,5 | |
| Installation category | Class II according to EN 61010-1 | |
| Environmental conditions | Temperature Rel. Hum. 80% up to 31°C with linear | |
| | decrease up to 50% at 40°C | |
| IP grade | IP 22 | |
| CE-compliant | EMC (EN 61326-1) | |
| | LV (EN 61010-1 EN 61010-2-040) | |
| | 2017/745/UE Medical Device Regulation | |
| | Risk Class I according to the rule 13 to the MDR | |
| Overheat switch : Automatic bimetallic Thermostat or | perating at 140°C fixed on the heating element | |

Overheat switch: Automatic bimetallic Thermostat operating at 140°C fixed on the heating element


Approximately Internal Tank Dimensions

External Appliance Dimensions

| W/D/H (mm) | 240 / 140 / 100 | W/D/H (mm) | 270 / 170 / 260 |
|-------------------------|-----------------|---------------------------|-----------------|
| Max filling volume tank | 3 L | Max operating tank volume | 2,35 L |

Constructive Materials

| Housing | Stainless steel AISI 304 |
|---------|--------------------------|
| Tank | Stainless steel AISI 304 |



Control panel available series



manual operation up to 1 hour of continuous. No heating system

Sweep System generator

the SONICA range is equipped with with a timer which can be set for 15 a timer which can be set for 15 minutes. It can also be set to manual minutes. It can also be set to operation up to 1 hour of continuous. The thermostat for the heater is set at 60°C.

Sweep System generator

temperature controlled electronically advanced of the SONICA range: by a microprocessor.

minutes. Double washing times 10-20-30 minutes by minutes key

Sweep System generator

M serie: The simplest version in MH serie: This version is equipped ETH serie: Cleaning times and EP serie: The most technologically

Sweep System generator; modern Ultrasonic cleaning times 5-10-15 digital display control panel window; degas time setting; cleaning times from 0 to 99 minutes; tank liquid pressing twice the temperature setting up to 70°C; memory for 9 cleaning programmes; jet program function to start quickly and easily cleaning cycle.

SOLTEC Srl - Via G.Rontgen 16 - 20136 Milano - Italy- Tel +39 0258308378 - Fax +39 0258308595 info@soltec.it https://www.soltec.it

Facebook https://www.facebook.com/soltec.ultrasonics LinkedIn https://www.linkedin.com/company/soltec-srl